

全自动电子花样机 ELECTRONIC PATTERN SEWING MACHINE

采用先进的彩色触摸屏技术，快速调节大压脚的角度，耗电低，存储能力强。

Adopts advanced color LED touch screen, the big presser foot's angle can be quickly and easily adjusted. Energy saving and powerful data storage.



ZJ5770A-1510HF1

高速电子花样机
ELECTRONIC PATTERN SEWING MACHINE

特种机系列
SPECIAL FUNCTION SERIES

-  作为电子循环缝缝机它实现了2800rpm的最高缝制速度；
The machine achieves the highest sewing speed of 2800rpm for a computer-controlled cycle machine.
-  通过脉冲马达驱动，抬压脚的动作比原来的缩短了1/4；
The stepping motor drive, the work clamp lifter's operating time has been reduced to one-fourth that of the conventional device.
-  有效防止启缝时的跳线及布料反面“鸟巢”现象；
The new thread clamp design makes the performance more stable.
-  功能强大的智能闭环电控系统。
The bottom thread clamp design, efficiently reduces the bottom thread problem of the light material.
-  提高送布精度，减少高速缝制的偏重面料时的缝制偏差现象。
Improve the feed precision, deduct the sewing deviation when sewing in high speed.

压脚方式可根据作业用途选择最合适的类型
The work clamp lifting method can be selected according to the application of your machine.

优质先进的伺服电机，穿刺力强，速度高，降低耗能
Advanced servo motor, low noise, high speed, reduce energy consumption.



	ZJ5770-1510HF1	ZJ5770-3020HF1	ZJ5770-2213HF1	ZJ5770A-1510	ZJ5770A-3020
缝纫范围 Sewing area	150mm (X)	300mm (X)	220mm (X)	150mm (X)	300mm (X)
	100mm (Y)	200mm (Y)	130mm (Y)	100mm (Y)	200mm (Y)
最高缝纫速度 Max. speed	2,500rpm(间距3mm 以上时) (Stitch length more than 3mm)		2,800rpm(间距3mm 以下时) (Stitch length less than 3mm)		

压脚方式可根据作业用途选择最合适的类型

The work clamp lifting method can be selected according to the application of your machine.



USB接口
快速传输



液晶显示屏 LCD display

采用7寸真彩液晶显示屏，用户可以使用手指或其他物体点触屏幕，完成相应的操作

7-inch color LCD screen, users can use fingers or other objects touch screen.



电脑控制系统 Computer control system

该产品采用世界先进的控制技术，多项技术指标达到国际同行标准。

The product uses advanced control technology, many technical indicators have reached international standard counterparts.



先进的无供油化技术防止了油污

Advanced dry technology prevents oil stains

针杆、挑线杆是通过润滑脂润滑，旋梭部则是由没槽提供微量机油。先进的无供油化技术，能确保缝品的洁净。

Needle bar unit and thread take-up unit is lubricated with grease, and the hook is fed with a minute quantity of oil from the oil tank. Advanced dry technology, protects your products from being stained with oil.

ZJ - 5770 A - 1510 - H - F - 1

5770:
series No.

无: 常规型 N0: Normal
A: 改进型 A: New type

缝制范围 Sewing area
1510: 150mmX100mm
2213: 220mmX130mm
3020: 300mmX200mm

H: 厚料 H: Heavy material
S: 标准 S: Standard material

脚踏板类型 1: 移动式踏板 2: 固定式踏板
Type of Foot PEDAL 1: Movement pedal 2: Fixation pedal

驱动类型

A: 电磁铁驱动压脚 B: 双气缸齐动式驱动分体式压脚
C: 双气缸分动式驱动压脚 D: 双气缸分动式+翻转驱动压脚
E: 双气缸分动式+专用可调整式驱动压脚
F: 双气缸分动式驱动压脚 (整体式压脚)
G: 双气缸分动式驱动压脚+伸缩驱动压脚 N: 快换模板
H: 双气缸齐动式驱动压脚+侧滑驱动压脚 K: 侧滑压脚

Type of driving

A: Electromagnet driving press foot
B: Double cylinder moving together driving press foot
C: Double cylinder moving separate driving press foot
D: Double cylinder moving separate & reversal driving press foot
E: Double cylinder integral & adjustable driving press foot
F: Double cylinder moving together driving press foot (integrated type)
G: Double cylinder moving together & flexible driving press foot
H: Double cylinder moving together & sideslip driving press foot